



KL 1500 compact

- Wide range power supply (85–264 V, 47–63 Hz).
- High frequency illumination (20 kHz, digital camera proof).
- Continuous dimming from 0 to 100%.
- High quality housing with integrated handle.
- Reasonable footprint and additional iron ballast to improve stability when used with goosenecks.
- Very low noise fan.
- High quality optical system including a prism lens for focusing.
- Filter slider with two positions (filter can remain in the light source even if it is not used).
- Lamphousing opens to the side (allows change of bulb even if stacked).
- Easy to use fixture mechanism with clamping screw.
- **Approvals:**
The KL 1500 compact has been approved and certified as laboratory equipment by CSA (C/US) and is in compliance with the CE regulations.
- Manufactured in the EU.

KL 1500 compact

Outstanding in price and functionality

The KL 1500 compact is a 150-watt halogen cold light source, developed and designed for industrial and life science applications in Stereo Microscopy and Macroscopy.

Consistently focusing on today's most important features allow an excellent price-performance-ratio.

The optical system is the same as used in the KL 1500 LCD and is optimized for coupling the light of the EFR-type halogen lamp into small diameter light guides.

KL 1500 compact


Type designation		General data	
Part-No.		150 300	
Dimensions (W x D x H)	(mm)/(inch)	183 x 261 x 137/7.2" x 10.3" x 5.4"	
Weight	(kg)	Approx. 3.0	
Cooling		Very low-noise fan	
Electrical data			
Operating voltage, frequency		90 – 264 V ~, 50 – 60 Hz	
Power consumption	(VA)	180	
Protection class		I	
Overvoltage category		II	
Lamp type		Halogen reflector lamp type EFR	
Lamp voltage rating	(V)	15	
Lamp power rating	(W)	150	
Average lamp	level 4	(h)	1500
Service life	level 5	(h)	200
Illumination data			
Light flux	(lm)	450	
Light control		Electrical	
Active light guide diameter	(mm)/(inch)	Max. 9/Max 0.35"	
Certification marks			
Approvals		CE, CSA	
EMV-class		A	

Power cords	Part-No.
IEC cord with European plug	400 051
IEC cord with US plug	400 052
IEC cord with UK plug	400 053
IEC cord with Swiss plug	400 054

Note: country specific power cord must be ordered separately!

Product improvements may result in specification or feature changes without notice.

KL 1500 compact



Lighting and Imaging
SCHOTT North America, Inc.
122 Charlton Street
Southbridge, MA 01550-1960
USA

Phone: +1 508/765-9744
Fax: +1 508/764-6273
lightingimaging@us.schott.com
www.us.schott.com/lightingimaging

SCHOTT
glass made of ideas

For your local sales contact please visit
www.us.schott.com/lightingimaging