



Model:  
**4083.SC10**

Typology:  
**Digital scanner**

Description:  
*Digital slide scanner, 10.000 dpi.*

### SCANNER SPECIFICATION

Signal output	USB 2.0
Illumination	LED
Scan quality	Normal, Quality (high)
Scan Color Depth	8 BIT, 16 BIT
Resolution	5.000 dpi in Normal mode, 10.000 dpi in Quality mode
Sensor	Linear array color CCD
Allowed Slide	Standard 24 x 75 mm
Scan view size	Any size, Max 24 x 36mm
Image format	JPG, TIFF
Prescan function time	25 seconds
Scanning time Normal quality	1min 30sec (24 x 36mm)
Scanning time Normal quality	40 sec (standard 15x15mm cover slide)
Image resolution Normal quality	7184 x 4786 pixels
Image size Normal quality	About 2 mega (24 x 36mm) JPG mode, 8BIT
Image size Normal quality	About 1 mega (15 x 15mm) JPG mode, 8BIT
Scanning time High quality	2min 10sec (24 x 36mm)
Scanning time High quality	1min (standard 15x15mm cover slide)
Image resolution High quality	14368 x 9572 pixels
Image size High quality	About 40 mega (24 x 36mm) JPG mode, 8BIT
Image size High quality	About 20 mega (15 x 15mm) JPG mode, 8BIT

### ACCESSORIES

Always Included	1.5 m USB cable, power supply, CD rom
-----------------	---------------------------------------

### SOFTWARE SPECIFICATION

System requirements	Windows XP service pack 2, Vista / win7 / win8 / win10 / 32-64 bit / usb 2.0
Supplied Software	Multilanguage software for image scan
Driver types	Installed by the software
Capture features	Prescan, slide scan 24x36mm, Crop scan, brightness, contrast, saturation, image flip

### GENERAL SPECIFICATION

Working temperature	-10 up to + 60°C
Storage temperature	-10 up to + 60°C
Relative Humidity	40% up to 90%
Dimensions	28 x 18 x 8,5 cm
Weight	1040 gr